



STYROFOAM™ BRAND DECKMATE™ PLUS EXTRUDED POLYSTYRENE FOAM INSULATION

1. PRODUCT NAME

STYROFOAM™ Brand
DECKMATE™ Plus Extruded
Polystyrene Foam Insulation

2. MANUFACTURER

The Dow Chemical Company
Dow Building Solutions
200 Larkin
Midland, MI 48674
1-866-583-BLUE (2583)
Fax 1-989-832-1465

Dow Chemical Canada ULC
Dow Building Solutions
450 – 1st St. SW, Suite 2100
Calgary, AB T2P 5H1
1-866-583-BLUE (2583) (English)
1-800-363-6210 (French)

www.dowbuildingsolutions.com

3. PRODUCT DESCRIPTION

BASIC USE

STYROFOAM™ Brand DECKMATE™ Plus Extruded Polystyrene Foam Insulation is designed specifically to provide a higher compressive strength and additional membrane support for conventional low slope roof applications. STYROFOAM™ Brand DECKMATE™ Plus Insulation is an extruded polystyrene foam. The board has smooth, high-density skins, with a closed cellular structure. STYROFOAM™ Brand DECKMATE™ Plus Insulation has excellent insulating characteristics (R-value of 5.0 [.88 RSI] per inch of thickness), low water absorption and excellent compressive strength.

Properties imparted by Dow's extrusion process coupled with the hydrophobic nature of polystyrene give STYROFOAM™ extruded polystyrene insulation high resistance to both water and water vapor. Durable and reusable, it exhibits dependable and predictable long-term mechanical and thermal performance, even in the most severe environments.

4. TECHNICAL DATA

APPLICABLE STANDARDS

STYROFOAM™ Brand DECKMATE™ Plus Insulation meets ASTM C578, Type IV – Standard Specification for Rigid Cellular Polystyrene Thermal Insulation. Applicable standards include:

- C518 – Standard Test Method for Steady State Thermal Transmission Properties by Means of the Heat Flow Meter Apparatus
- D1621 – Standard Test Method for Compressive Properties of Rigid Cellular Plastics
- C272 – Standard Test Method for Water Absorption of Core Materials for Structural Sandwich Constructions
- E96 – Standard Test Methods for Water Vapor Transmission of Materials
- C203 – Standard Test Methods for Breaking Load and Flexural Properties of Block Type Thermal Insulation
- D2126 – Standard Test Method for Response of Rigid Cellular Plastics to Thermal and Humid Aging
- E84 – Standard Test Method for Surface Burning Characteristics of Building Materials
- CAN/ULC S701, Type 3

CODE COMPLIANCES

STYROFOAM™ Brand DECKMATE™ Plus Insulation complies with the following codes:

- Meets IBS/IRC requirements for foam plastic insulation; see ICC-ES ESR-2142
- Underwriters Laboratories, Inc. (UL) Classified, see Classification Certificate D369

PHYSICAL PROPERTIES

STYROFOAM™ Brand DECKMATE™ Plus Extruded Polystyrene Foam Insulation exhibits the properties and characteristics indicated in Tables 3 and 4 when tested as represented.

Exposure to ultraviolet radiation in sunlight for several weeks will cause the surface of STYROFOAM™ Brand DECKMATE™ Plus Insulation to become yellow and dusty. A light-colored, opaque protective covering should be used if excessive solar exposure is expected. The surface degradation will have no measurable effect on the insulating value of the plastic foam unless the deterioration is allowed to continue until actual foam thickness is lost. Since the dust would impair the performance of adhesives and finishes, the dusty surface should be brushed off before these products are applied.

ENVIRONMENTAL DATA

STYROFOAM™ Brand DECKMATE™ Plus Insulation is manufactured with proprietary blowing agent with zero percent ozone depletion potential.

STYROFOAM™ Brand DECKMATE™ Plus Insulation is reusable in many applications.

FIRE PROTECTION

STYROFOAM™ Brand DECKMATE™ Plus Insulation is combustible; protect from high heat sources. Local building codes may require a protective or thermal barrier. For more information, consult MSDS, call Dow at 1-866-583-BLUE (2583) or contact your local building inspector.

5. INSTALLATION

STYROFOAM™ Brand DECKMATE™ Plus Insulation can be used over any substrate in new construction for thermal upgrading of existing roofing when reroofing is required. Roof substrate must be clean, dry, smooth and free from oil, grease, rust, frost and snow.

The roof system must be designed to meet all applicable building codes.

Flute spanability – maximum flute spanability is 1-3/4" for 1" product, 3" for 1-1/2" product, 4-3/8" for 2" product or greater.

Caution: Use a temporary white covering over dark membranes or immediately cover with pavers or stone to prevent excessive heat exposure to the foam board.

Boards of STYROFOAM™ Brand DECKMATE™ Plus Insulation are easy to handle, cut and install. Contact a local Dow representative or access the literature library: www.dowbuildingsolutions.com

6. AVAILABILITY

STYROFOAM™ Brand DECKMATE™ Plus Insulation is manufactured in several locations

across North America and is distributed through an extensive network. For more information, call: 1-800-232-2436 (English) 1-800-565-1255 (French)

7. WARRANTY

In the United States, a 50-year thermal limited warranty is available on STYROFOAM™ Insulation products 1.5 inches and greater. For thickness less than 1.5 inches, other warranties may apply. Warranties are available as described at <http://building.dow.com/na/en/tools/warranty.htm>

8. MAINTENANCE

Not applicable.

9. TECHNICAL SERVICES

Dow can provide technical information to help address questions when using STYROFOAM™ Brand DECKMATE™ Plus Insulation. Technical personnel are available to assist with any insulation project. For technical assistance, call: 1-866-583-BLUE (2583) (English) 1-800-363-6210 (French)

10. FILING SYSTEMS

- www.dowbuildingsolutions.com
- www.sweets.com

TABLE 1: U.S. SIZES, R-VALUES AND EDGE TREATMENTS FOR STYROFOAM™ BRAND DECKMATE™ PLUS EXTRUDED POLYSTYRENE FOAM INSULATION

NOMINAL BOARD THICKNESS ⁽¹⁾ , IN.	R-VALUE ⁽²⁾	BOARD SIZE, FT	EDGE TREATMENT
2.0	10.0	2 x 8, 4 x 8	Square Edge
2.5	12.5	4 x 8	Square Edge
3.0	15.0	2 x 8, 4 x 8	Square Edge
4.0	20.0	2 x 8, 4 x 8	Square Edge

(1) Not all product sizes are available in all regions.

(2) R means resistance to heat flow. The higher the R-value, the greater the insulating power. R-values are expressed in ft² • h²•F/Btu. RSI values are expressed in m²°C/W. R-value determined by ASTM C518.

TABLE 2: CANADIAN SIZES, R-VALUES AND EDGE TREATMENTS FOR STYROFOAM™ BRAND DECKMATE™ PLUS EXTRUDED POLYSTYRENE FOAM INSULATION

NOMINAL BOARD THICKNESS ⁽¹⁾ , MM	R-VALUE	BOARD SIZE, MM	EDGE TREATMENT
4 in (102 mm)	20.0	600 x 2400	Shiplap Edge

(1) Not all product sizes are available in all regions.

TABLE 3: TYPICAL PHYSICAL PROPERTIES (U.S.) OF STYROFOAM™ BRAND DECKMATE™ PLUS EXTRUDED POLYSTYRENE FOAM INSULATION

PROPERTY AND TEST METHOD	VALUE
Thermal Resistance per inch, ASTM C518 @ 75°F mean temp., ft ² •h•°F/Btu, R-value ⁽¹⁾ , min.	5.0
Compressive Strength ⁽²⁾ , ASTM D1621, psi, min.	25
Water Absorption, ASTM C272, % by volume, max.	0.3
Water Vapor Permeance ⁽³⁾ , ASTM E96, perm, max.	1.5
Maximum Operating Temperature, °F	165
Coefficient of Linear Thermal Expansion, in/in•°F	3.5 x 10 ⁻⁵
Flexural Strength, ASTM C203, psi, min.	50
Dimensional Stability, ASTM D2126 / CAN/ULC S701, % linear change, max.	2.0
Flame Spread ⁽⁴⁾ , ASTM E84	15
Smoke Developed, ASTM E84	165

- (1) R means resistance to heat flow. The higher the R-value, the greater the insulating power.
- (2) Vertical compressive strength is measured at 10 percent deformation or at yield, whichever occurs first.
- (3) Based on 1" thickness.
- (4) This numerical flame spread rating is not intended to reflect hazards presented by this or any other material under actual fire conditions.

TABLE 4: TYPICAL PHYSICAL PROPERTIES (CANADIAN) OF STYROFOAM™ BRAND DECKMATE™ PLUS EXTRUDED POLYSTYRENE FOAM INSULATION

PROPERTY AND TEST METHOD	VALUE
Thermal Resistance per inch (25 mm), ASTM C518 @ 75°F (24°C) mean temp., ft ² •h•°F/Btu, (m ² •°C/W), R-value (RSI) ⁽¹⁾ , min.	5.0 (0.87)
Compressive Strength ⁽²⁾ , ASTM D1621, psi (kPa), min.	20 (140)
Water Absorption, ASTM D2842, % by volume, max.	0.7
Water Vapour Permeance ⁽³⁾ , ASTM E96, perm (ng/Pa•s•m ²), max.	1.5 (90)
Maximum Use Temperature, °F (°C)	165 (74)
Coefficient of Linear Thermal Expansion, in/in•°F (mm/m•°C)	3.5 x 10 ⁻⁵ (6.3 x 10 ⁻²)
Flexural Strength, ASTM C203, psi, (kPa), min.	43.5 (300)
Dimensional Stability, ASTM D2126 / CAN/ULC S701, % linear change, max.	1.5

- (1) R means resistance to heat flow. The higher the R-value or RSI, the greater the insulating power.
- (2) Vertical compressive strength is measured at 10 percent deformation or at yield, whichever occurs first.
- (3) Based on 1" (25 mm) thickness.

www.dowbuildingsolutions.com**Technical Information**

1-866-583-BLUE (2583) (English)
1-800-363-6210 (French)

Sales Information

1-800-232-2436 (English)
1-800-565-1255 (French)

IN THE U.S.

THE DOW CHEMICAL COMPANY
200 Larkin
Midland, MI 48674

IN CANADA

DOW CHEMICAL CANADA ULC
450 – 1st St. SW • Suite 2100
Calgary, AB T2P 5H1

NOTICE: No freedom from any patent owned by Dow or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, Customer is responsible for determining whether products and the information in this document are appropriate for Customer's use and for ensuring that Customer's workplace and disposal practices are in compliance with applicable laws and other government enactments. The product shown in this literature may not be available for sale and/or available in all geographies where Dow is represented. The claims made may not have been approved for use in all countries or regions. Dow assumes no obligation or liability for the information in this document. References to "Dow" or the "Company" mean the Dow legal entity selling the products to Customer unless otherwise expressly noted. NO EXPRESS WARRANTIES ARE GIVEN EXCEPT FOR ANY APPLICABLE WRITTEN WARRANTIES SPECIFICALLY PROVIDED BY DOW. ALL IMPLIED WARRANTIES INCLUDING THOSE OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED.

CAUTION: This product is combustible. Protect from high heat sources. A protective barrier or thermal barrier may be required as specified in the appropriate building code. For more information, consult MSDS, call Dow at 1-866-583-BLUE (2583) or contact your local building inspector. In an emergency, call 1-989-636-4400 in the U.S. or 1-519-339-3711 in Canada.

Building and/or construction practices unrelated to building materials could greatly affect moisture and the potential for mold formation. No material supplier including Dow can give assurance that mold will not develop in any specific system.

